




RRT-PMC-CF-F-A PMC Compact Flash Module: Air Cooled


THE **PMC FIXED COMPACT FLASH MODULE: AIR COOLED** is a PMC mezzanine storage module with a PCI ATA/IDE controller that supports one fixed Compact Flash.

Provides boot drive and/or disk storage for VPX, VME, cPCI and ATCA single board computers (SBCs) with PMC Slot.

- PMC PCI 32-bit data at 33MHz per IEEE 1386-2001
- Transfer rates up to 133 MB/s
- Capacities up to 512GB
- Air cooled
- Wide range of COTS Compact Flash options
- Compact Flash drive secured by rugged retainer clip
- Compatible with all SBCs with a PMC slot
- Meets PMC IEEE 1386-2001 height requirements
- 3.3V and 5V PCI interface compliant
- Compact Flash with write protect switch available
- Front panel activity LEDs
- VxWorks, Linux, and Windows driver support
- ROHS compliant



Parhelia B.V.
www.parheliabv.com
☎ +31(0)10 741 00 28



Ordering Information

PMC Compact Flash Module: Air Cooled

RRT-PMC-CF-F-A-UR

Options May be left blank

Conformal Coating

UR	Polyurethane
AR	Acrylic

ORDER EXAMPLES

RRT-PMC-CF-F-A-UR
RRT-PMC-CF-F-A-AR

Compact Flash Drive

RRT-CF-SLC - 512GB - WP

Options May be left blank

Write Protect

WP	Write Protect
----	---------------

Capacity

2GB - 64GB	SLC
8GB - 512GB	MLC

NAND Flash Type

SLC	Single Level Cell
MLC	Multi Level Cell

ORDER EXAMPLES

RRT-CF-MLC-512GB
RRT-CF-SLC-60GB-6
RRT-CF-MLC-128GB-WP



Parhelia B.V.
www.parheliabv.com
+31(0)10 741 00 28

Product Specifications

PMC COMPACT FLASH MODULE: AIR COOLED

PERFORMANCE

CAPACITIES	Up to 512GB
PMC INTERFACE	PMC PCI 32-bit data at 33MHz per IEEE 1386-2001
PMC INTERFACE SPEED	133 MB/s
COMPACT FLASH INTERFACE	IDE/ATA
SECTOR SIZE	512 bytes

RELIABILITY

MTBF - PMC MODULE ¹	3 million hours
--------------------------------	-----------------

POWER

VOLTAGE	+5V +/- 5%; Voltage 3.3 +/- 0.3V
WATTS (IDLE)	1.2 W
WATTS (ACTIVE)	2.5 W

ENVIRONMENTAL

OPERATING TEMP., VITA 47 CLASS	0 °C to 70 °C
STORAGE TEMP.	-40 °C to 85 °C
ALTITUDE	80,000 ft. (24,000 meters)
RELATIVE HUMIDITY	5% to 95% non-condensing
SHOCK, VITA 47 CLASS	40g, 11 millisecond terminal sawtooth pulse
VIBRATION, VITA 47 CLASS	0.1g ² /Hz

PHYSICAL

FORM FACTOR	PMC
WEIGHT	3.2 oz. /91g max

NOTES

(1) Telcordia SR-322, Issue 3, operating temp (40C), electrical stress (50%), environmental factor (1.0).



Parhelia B.V.
www.parheliabv.com
☎ +31(0)10 741 00 28



Red Rock Technologies, Inc. reserves the right to modify, change or discontinue specific products within its product line at its own discretion. Red Rock Technologies, Inc. does not assume any liability resulting from the application or use of its products. The information contained herein has been checked and is believed to be entirely accurate; however, no responsibility is assumed for inaccuracies. "Red Rock Technologies" and the mountain logo are registered trademarks of Red Rock Technologies, Inc.

© Copyright 2023 Red Rock Technologies, Inc.
All rights reserved. (Rev. 20230113a)